

IN THE CLAIMS

1. (currently amended) A ~~t~~ Twin-wire press ~~(2)~~ for dewatering of a fiber suspension, comprising lower rolls ~~(4)~~, an endless lower wire that runs around the lower rolls, upper rolls ~~(6)~~ and, an endless upper wire that runs around the upper rolls, ~~further the twin-wire press comprises a first (8, 8') dewatering table and a second (10, 10') dewatering table, respectively, which supportings the respective upper and lower wires, respectively, the~~ dewatering tables forming a wedge-shaped dewatering space (12) between the upper and lower wires in the longitudinal direction (11) of the twin-wire press for initial pressing and dewatering of the fiber suspension entering the dewatering space, for to formation of a fiber web of the dewatered fiber suspension between the wires, and a roll arrangement (14) positioned after the dewatering tables, seen in the direction of movement (F) of the wires, for final pressing and dewatering of the fiber web between the wires, the roll arrangement being ~~is~~ provided in a press frame ~~(16)~~, and that a press and lift arrangement ~~(18) is arranged to the first dewatering table (8, 8') for vertically adjusting the first dewatering table, characterised in that and a link system (20) is joined at arranged in a first~~ end with a joint (22) to at the press frame (16) and joined at a second end of the link system via a second in another end arranged with a joint (24) at an upper section (26) of the first dewatering table (8, 8'), where in by the first dewatering table (8, 8') along its whole longitudinal extension (L2) can be is movable in the direction (T) from and against the second dewatering table by movement by means of the press and lift arrangement (18).

2. (currently amended) The twin-wire press according to claim 1, ~~characterised wherein in that~~ an end section of the press and lift arrangement (18) is fixed to the press frame (16) and a second end section of the press and lift arrangement (18) is arranged to the first dewatering table (8, 8').

3. (currently amended) The twin-wire press according to claim 2, ~~wherein characterised in that~~ the press and lift arrangement (18) is arranged in the vicinity of a front edge (32) of the first dewatering table (8, 8').

4. (currently amended) The twin-wire press according to claim 2 ~~or 3~~, ~~wherein characterised in that~~ one end of the press and lift arrangement is connected to a projecting section (34) of the press frame (16), in connection to an upper section (26) of the first dewatering table at a distance from the dewatering space (12).

5. (currently amended) The twin-wire press according to ~~any of the preceding claims 1~~, ~~wherein characterised in that~~ the press frame (16) comprises a stop member (36) arranged on a surface (38) of the press frame in at the space defined by between the press frame and the front edge (32) of the upper table, opposite the upper table.

6. (currently amended) The twin-wire press according to ~~any of the preceding claims 1~~, ~~wherein characterised in that~~ the press and lift arrangement (18) comprises a hydraulic cylinder.

7. (currently amended) The twin-wire press according to ~~any of the preceding claims 1~~, ~~wherein characterised in that~~ the link system (20) comprises a link arm (40) that in one end is pivotally arranged in said joint (24) at the first dewatering table, and in a second end pivotally arranged in said joint (22) at the press frame (16).

8. (currently amended) The twin-wire press according to any

~~of the preceding claims 1, wherein characterised in that the~~
twin-wire press comprises said link system (20) and press and
lift arrangement (18) on each side of the twin-wire press (2).

9. (currently amended) The twin-wire press according to any
~~of the preceding claims 1, wherein characterised in that the~~
first dewatering table is an upper dewatering table (8) and the
second dewatering table is a lower dewatering table (10).